SMSC Status Codes:

CODE	REASON	DESCRIPTION
I) FINAL S	STATUS	
-01	New Error Code	This status displays when the error code provided by the subscribers terminating operator is not mapped with the existing status.
000	Sub-SMSC	The message is on SMSC queue i.e. the message has been inserted into the SMSC database but the status of the message is yet to be received.
001	DELIVRD	Successfully delivered.
002	FAILED	The message is permanently failed due to CallBarred, Error in Destination Number, Error in TeleService Provider etc.
004	NDNC_Failed	Failed Due to DND Registration
005	Blacklist	Black-listed number. This list of numbers is provided by the Customer and includes numbers of CEO etc. A message will never go to a number in the black-list.
006	Whitelist	This error is received when a Opt-In account sends messages to a non-white listed number
007	Invalid Series	This error is shown when a number series in the correct number format is invalide.
008	Prepaid Reject	This error is shown when the messages are rejected due to insufficient credits.
009	Night Expiry	Promotional messages blocked after 9 PM
031	EXP-AbsSubs	The message is rejected because there was no paging response, the IMSI record is marked detached, or the MS is subject to roaming restrictions.
032	EXP-MEM-EXCD	Message rejected because the MS doesn't have enough memory.
033	EXP-NW-FAIL	Message rejected due to network failure.
034	EXP-NW-TMOUT	Message rejected due to network or protocol failure.
035	EXP-SMS-TMOUT	Message rejected due to network or protocol failure.
036	EXP-HDST-BUSY	The message is rejected because of congestion encountered at the visited MSC.

037		Message queue exceeded when there are too many messages for one number. SMSC can deliver only a particular number of messages to a mobile number. If there are more messages, they get this error code till the queue clears.
044	Promo_blocked	Promotional messages blocked.

II) INTERM	MEDIATE DELIVERY REP	ORT
110	PENDG-ABS-SUB	The message is rejected because there was no paging response, the IMSI record is marked detached, or the MS is subject to roaming restrictions at the first attempt.
120	PENDG-MEM- EXCD	Message rejected because the MS doesn't have enough memory when at the first attempt.
130	PENDG-NW- FAILR	Message rejected due to network failure at the first attempt.
140	PENDG-NW-TMOUT	Message rejected due to network or protocol failure at the first attempt.
150	PENDG-SMS- TMOUT	Message rejected due to network or protocol failure at the first attempt.
160	PENDG-HDST- BUSY	The message is rejected because of congestion encountered at the visited MSC at first attempt.
200	REMOTE NODE NOT REACHABLE	Remote HLR or VLR route is not defined on adjacent node
210/190	User Abort	TCAP Protocol abort received from one of the node on the network